

KROY®

K4452/K4453

COMPACT DESKTOP PRINTERS

The new K4452 and K4453 series of entry level label printers are ideal for low to medium volume label printing. With a small footprint and packed with features these new printers offer versatile label printing solutions.

The new clamshell design gives easy access to the print head for cleaning and makes label and ribbon loading simple.



Features include..

LabelView XLT+, Windows driver for 95, 98, NT, 2000, XP
Sensors: Label gap, Reflective (position adjustment), Head open

Technical specification:

Size: 205mm (W) x 185mm (H) x 310mm (L)
Weight: 3.2Kg
Memory: Flash ROM (1Mb), DRAM (2Mb)
Interface: RS232 (Max. baud rate 19,200 bps)
Parallel: SPP/ECP(TBD)
USB 1.1
Storage: -10 - 60°C

UL, CUL, TUV, C-Tick, (power supply only)
CE class B (EN60950), EN55022, EN55024,
EN1000-3-2, EN61000-3-3), FCC class B, VCCI
Power: 100-240V Universal switching power
supply (external adapter)
Operation: 5 - 40°C
Humidity: 20 - 95%

Font: Five alpha-numeric fonts, Outline font, OCR-A, OCR-B, Barcode 39, 39C 93, 128UCC, 128 subsets A, B, C,
Code 11 Codabar, Interleave 2 of 5, EAN-8, 13, 128, UPC-A, UPC-E, EAN and UPC 2(5) digitals add-on, MSI,
Plessey, Postnet, 2D barcode PDF-417, Maxicode, DataMatrix, MicroPDF417

Options:

Cutter: full, 116mm width
Paper thickness 0.2mm 100g/m², MCBF 500,00, Paper thickness 0.25mm 280g/m², MCBF 250,00
KP200 keyboard display unit, external LAN adapter, external memory card (1Mb to 4Mb)
Liner less printing capability, external roll mount OD 214mm with 25mm core)

Printing

Thermal transfer/direct thermal printing
Resolution: K4452: 8 dots per mm - 203dpi
K4453: 12 dots per mm - 300dpi
Print speed: 2, 3, 4, 5 ips selectable, 2, 3, ips for peeler function

Max. print width: 108mm
Max. print length: 999mm depending on user
software application
Ribbon: 300m (max.)

Media:

Roll fed, die-cut, continuous or fan fold with guide
Media thickness: 0.06mm - 0.25mm
Media width: 19 - 118mm and 19 - 60mm
Media length: 10-999mm (without peel and cutter 6 - 999mm)
Supply roll holder: Internal

Ribbons: Kroy Wax, Wax/resin and Resins
Interface: USB, Parallel and RS232
Operating temperatures: 5°C - 35°C
Roll core diameter: 25.4mm

Our recommendations on the use of our products are based on test data believed to be reliable, but we would ask that you conduct your own tests to determine the suitability for your application. Kroy cannot accept any liability, direct or consequential for loss or damage caused as a result of our recommendations. Specifications and pricing may change at any time without notice. Subject to product availability. ©1994 Kroy (Europe) Ltd. Kroy and DuraType are registered trademarks of Kroy Inc.

KROY®

Kroy (Europe) Limited
Worton Grange, Reading, Berkshire
RG2 0LZ England
Tel +44 (0)118 9865 200 Fax +44 (0)118 9865 205
www.kroyeurope.com e-mail info@kroyeurope.com

France
Service Commercial Tel +33 1 48 69 58 18
Germany
Kundendienst Tel +49 2464 907142

